

Application Serial No: 10/657,774
In reply to Office Action of 21 September 2004

Attorney Docket No. 83084

Amendment to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (cancelled)

2. (cancelled)

3. (currently amended) [[The]] An adjustable apparatus according to claim 2 for supporting a long span specimen in a flexure test by a load application device, said apparatus comprising:

an upper structure including an I-shaped elongated beam, at least one support bracket adjustably mountable along a longitudinal span thereof, and a saddle pivotally mounted in said at least one upper support bracket, said saddle engageable in support of the specimen and said upper structure engageable with the load application device opposite said saddle wherein said upper structure includes a plurality of spaced and paired apertures formed as pairs in at least one end plate bordering an inner plate of said [[I-shape]] I-shaped elongated beam such that one

RECEIVED
CENTRAL FAX CENTER
OCT 28 2004

Application Serial No: 10/657,774
In reply to Office Action of 21 September 2004

Attorney Docket No. 83084

aperture in each pair is on an opposite side of said
inner plate; and

a lower structure spaced apart from said upper structure,
said lower support structure including a support
beam, at least one spacing member adjustably mounted
along a longitudinal span thereof, a lower support
bracket adjustably mounted along a longitudinal span
of said spacing member, and a saddle pivotally
mounted in said lower support bracket to face said
upper support structure and engageable with the
specimen.

4. (currently amended) The apparatus according to claim 3
wherein said upper support bracket includes a plurality of
spaced and paired apertures at a base portion of said upper
~~mounting~~ support bracket, said apertures of said upper
~~mounting~~ support bracket alignable with said apertures of said
end plate and;

said upper ~~mounting~~ support bracket further including a
receiving slot formed on opposing side walls of said
bracket for supporting said saddle.

5. (original) The apparatus according to claim 4 wherein
said saddle includes a pin protruding from opposite sides of

Application Serial No: 10/657,774
In reply to Office Action of 21 September 2004

Attorney Docket No. 83084

said saddle, each pin pivotal in a corresponding receiving slot of said side walls.

6. (currently amended) The apparatus according to claim 5 further comprising a securing plate mountable on each side wall of said upper ~~mounting~~ support bracket, said securing plate securing said pins within said receiving slots.

7. (cancelled)

8. (currently amended) ~~[[The]]~~ An adjustable apparatus according to claim 7 for supporting a long span specimen in a flexure test by a load application device, said apparatus comprising:

an upper structure including an elongated beam, at least one support bracket adjustably mountable along a longitudinal span thereof, and a saddle pivotally mounted in said at least one upper support bracket, said saddle engageable in support of the specimen and said upper structure engageable with the load application device opposite said saddle; and

a lower structure spaced apart from said upper structure, said lower support structure including a I-shaped support beam, at least one spacing member adjustably mounted along a longitudinal span thereof, a lower

Application Serial No: 10/657,774
In reply to Office Action of 21 September 2004

Attorney Docket No. 83084

support bracket adjustably mounted along a longitudinal span of said spacing member, and a saddle pivotally mounted in said lower support bracket to face said upper support structure and engageable with the specimen wherein said lower structure includes a plurality of spaced and paired apertures formed as pairs in at least one end plate bordering an inner plate of said ~~I-shape of said lower structure~~ I-shaped support beam such that one aperture in each pair is on an opposite side of said inner plate.

9. (original) The apparatus according to claim 8 wherein said lower support bracket further comprises a slider as a base portion center mounted at a distal end of a leg portion, and a pair of side walls projecting from opposite sides of said base portion, each side wall of said slider including a receiving slot formed therein for supporting said saddle of said lower structure.

10. (original) The apparatus according to claim 9 wherein said saddle of said lower structure includes a pin protruding from opposite sides of said saddle, each pin pivotable in a corresponding receiving slot of said side walls.

Application Serial No: 10/657,774
In reply to Office Action of 21 September 2004

Attorney Docket No. 83084

11. (original) The apparatus according to claim 10 wherein said lower structure further includes a spacer member normal to said longitudinal span of said lower structure and including a first portion of said spacer adjustably secured to the apertured surface of said lower structure and a second portion opposite the first portion adjustably supporting said leg of said slider.

12. (original) The apparatus according to claim 11 further comprising a plate mechanism mechanically attachable to said spacer and interposing extending protrusions of said leg portion therebetween.

13. (original) The apparatus according to claim 11 wherein said lower support bracket is slidably adjustable relative to said spacer and said spacer is slidably adjustable relative to said lower structure.

14. (original) The apparatus according to claim 12 wherein said lower support bracket is slidably adjustable relative to said spacer and said spacer is slidably adjustable relative to said lower structure.

15. (original) The apparatus according to claim 12 wherein said plate mechanism includes a spacer plate superposed by a

Application Serial No: 10/657,774
In reply to Office Action of 21 September 2004

Attorney Docket No. 83084

fixing plate, said spacer plate being mounted directly on the opposite surface of said spacer.

16. (cancelled)

17. (cancelled)

18. (original) An adjustable apparatus for supporting a long span specimen in a flexure test by a load application device, said apparatus comprising:

an upper structure including an elongated beam, at least one support bracket adjustably mountable along a longitudinal span thereof, and a saddle pivotally mounted in said at least one upper support bracket, said saddle engageable in support of the specimen and said upper structure engageable with the load application device opposite said saddle; and

a lower structure spaced apart from said upper structure, said lower support structure including a support beam, at least one spacing member adjustably mounted along a longitudinal span thereof, a lower support bracket adjustably mounted along a longitudinal span of said spacing member, and a saddle pivotally mounted in said lower support bracket to face said

Application Serial No: 10/657,774
In reply to Office Action of 21 September 2004

Attorney Docket No. 83084

upper support structure and engageable with the
specimen;

said upper structure including a plurality of spaced and
paired apertures formed as pairs in at least one end
plate bordering an inner plate of said I-shape of
said upper structure such that one aperture in each
pair is on an opposite side of the inner plate;

said upper support bracket further comprises a slider as
a base portion center mounted at a distal end of a
leg portion, and a pair of side walls projecting
from opposite sides of said base portion, each side
wall of said slider including a receiving slot
formed therein for supporting said saddle of said
upper structure.

19. (cancelled)